



INDUSTRIE LODDO

INNOVATIVE TANK SOLUTIONS

64010 CIVITELLA DEL TRONTO - ITALY -

Tel +39 0861 927003 - web: www.tmlgroup.it - P.I. 0077788675

Enamelled boiler

with a single fixed coil

Carbon steel enamelled (DIN 4753.3) Boiler for the production and storage of Hot Domestic Water equipped with internal fixed coil heat exchanger.

Insulation Hard Polyurethan 50 mm + PVC

Mod. 72.HYBRID300R

TECHNICAL INFO

Serial Nr.: 111920395

| | Material | Dimensions | P. max | T. max |
|-------------|----------|---------------------|--------|--------|
| Puffer Body | S 235 Jr | 45 L | 4 bar | 95 °C |
| Boiler Body | S235JR | 290.3 L | 8 bar | 95 °C |
| Bottom Coil | S235JR | 3.85 m ² | 12 bar | 95 °C |
| | -- | -- | -- | -- |
| | -- | -- | -- | -- |

Heat loss 68.2 W

Energy efficiency class B

Installation Rules:

Check for the "USER MANUAL AND TECHNICAL DOCUMENTATION" supplied with the product purchased, if missing, send a request for a copy to the Technical Office, quoting the serial number on the label. Before commissioning read the "USER MANUAL AND TECHNICAL DOCUMENTATION" attached.

Any form of warranty of the device expires if not observed strictly the installation specifications given in the "USER MANUAL AND TECHNICAL DOCUMENTATION".

Date: 05/11/19

Years of Warranty: 5



111920395



111920395

ATTENZIONE / WARNING / ACHTUNG :

Per garantire la giusta tenuta idraulica della flangia bisogna portare il bollitore nelle condizioni di temperatura e pressione di esercizio per un periodo di quattro ore e verificare che il serraggio delle viti sia compreso tra 30 e 32 Nm.

To ensure the correct seal of the flange must bring the boiler in the work conditions of temperature and pressure for a period of 4 hours and verify that the tightening of screws is between 30 and 32 Nm.

Um die Dichtheit des Flansches zu gewährleisten muss der Behälter auf Betriebstemperatur und Betriebsdruck gebracht und 4 Stunden lang so gehalten werden. Die Schrauben sind dabei zwischen 30 und 32 Nm anzuziehen.

| | | |
|---------------|-------------------------|----------------------|
| SAMTEC | Code | 72.HYBRID300R |
| | Bestellung/Order/Ordine | |

OOZZ72.HYBRID300R111920395



ENERG
енергия · ενέργεια

Y IJA
IE IA



72.HYBRID300R



68 W

290 L

2017

812/2013